





BAHAMA[®]

C4sun sails
Price List 2023



Models | Sails

		Width up to (in m)**		4.0	4.5	5.0	5.5	6.0	6.8	
No.	Product	Description	Price in €							
elips4sun*										
1	Projection up to (in m)**	4.5		- Four traction ropes and one mast	7,550	8,200	-	-	-	
2		5.0		- Organic design	8,100	8,500	8,900	-	-	
3		5.5		- Double sail possible	8,400	8,800	9,450	10,200	-	
4		6.0		- Clew with 1.8 or 2.7	8,700	9,350	9,950	10,600	10,800	
5		6.8			9,450	9,750	10,800	11,250	11,450	
square4sun cross*										
6	Projection up to (in m)**	4.0		- Two traction ropes, each with one mast	7,250	7,550	8,200	8,600	9,150	9,950
7		4.5		- Large shaded area	7,550	8,200	8,500	9,050	9,750	10,600
8		5.0		- Double sail possible	8,100	8,500	8,900	9,650	10,300	11,850
9		5.5			8,400	8,800	9,450	10,200	10,800	12,400
10		6.0			8,700	9,350	9,950	10,700	11,350	13,000
11		6.5			9,050	9,750	10,300	11,150	11,850	13,650
12		7.0			9,450	10,200	10,800	11,550	12,600	14,500
13		7.8			10,100	10,800	11,350	12,500	13,550	-
square4sun cross pro*										
14	Projection up to (in m)**	4.0		- Two traction ropes, each with one mast	7,750	8,100	8,700	9,150	9,750	10,500
15		4.5		- Particularly suitable for roof terraces and smaller areas due to shortened ropes	8,100	8,700	9,050	9,650	10,300	11,150
16		5.0		- Double sail possible	8,600	9,050	9,450	10,200	10,800	11,750
17		5.5			8,900	9,350	10,100	10,700	11,450	12,900
18		6.0			9,250	9,850	10,500	11,250	11,850	13,550
19		6.5			9,500	10,300	10,800	11,650	12,500	14,150
20		7.0			10,000	10,700	11,450	12,050	13,100	15,100
21		7.8			10,600	11,350	11,850	13,000	14,050	-
square4sun line*										
22	Projection up to (in m)**	4.0		- Four traction ropes with two masts	7,750	8,100	8,700	9,150	9,750	11,550
23		4.5		- Double sail possible	8,100	8,700	9,050	9,650	10,300	12,200
24		5.0			8,600	9,050	9,450	10,200	10,800	12,900
25		5.5			8,900	9,350	10,100	10,700	11,450	13,550
26		6.0			9,250	9,850	10,500	11,250	11,850	14,050
27		6.5			9,500	10,300	10,800	11,650	12,500	14,700
28		7.0			10,000	10,700	11,450	12,050	13,100	15,650
29		7.8			10,600	11,350	11,850	13,550	14,800	16,600

* All stated sail prices include roller tube with sail cloth and profiles, standard wall mount, and Somfy io tube motor with remote control or alternatively Somfy LT tube motor. Mast not included (see p. 3 for prices).

** Individual intermediate sizes possible.

For elips4sun: Projection dimension larger or equal to width dimension. Other dimensions on request.

The sail dimensions shown in red include the C4sun power package (2 synchronized Somfy Taurus motors); see numbers 87 – 88

Rec. sales prices (net) in euros, exclusive of VAT | Pricing ex works | Prices exclusive of packaging, shipping, and installation costs.

This price list is subject to the latest version of our General Terms and Conditions (GTCs).

Additional equipment | Sails

No.	Product	Description	Price in €
30	Sail material with special color	- WeatherMax 80 Sail material - Deviates from standard colors in C4sun color chart - Calculation: projection × width = m² - Available for every sail model	13.50 per m²
31	Winter protective cover	- For roller tube incl. sail - WeatherMax 80 - Color: graphite - With velcro fastening	298 per item




Models | Mast

No.	Product	Description	Dimensions/ technical data	Price in € per item
32	ID 110	- Round profile, dia. 110 mm - Powder-coated aluminum RAL 9006 or 7016, textured matte finish - Damper-controlled - With wind pressure relief - Installation angle: approx. 82 – 90° - Max. projection: 5,800 mm - Standard height: 3,627 mm; height of hitching point: 2,800 mm, at least 700 mm installation depth - Not suitable for elips4sun	Height: - 3,627 mm - Special sizes on request	1,600
33	ID 175	- Oval profile with 4 edges: 175 mm, 75 – 105 mm - Powder-coated aluminum RAL 9006 or 7016, textured matte finish - Damper-controlled - With wind pressure relief - Installation angle: 0 – 90° possible - Lengths exceeding 4,000 mm must be anchored – see anchoring set, item no. 53	Height: - 3,000 mm, 3,500 mm - 4,000 mm, 4,500 mm - Special sizes up to 7,000 mm	3,250 3,350 On request
34	IG 101	- Round profile, dia. 101.6 mm - V2A stainless steel - Internal weight - With wind pressure relief - Installation angle: 90° - Exclusively for square4sun cross & cross pro up to 7.2 m projection length; for square4sun line up to 6.2 m projection length	Height: 5,240 mm, 5,850 mm	2,800
35	IG 211	- Square profile, 211 mm - V2A stainless steel - Internal weight - With wind pressure relief - Installation angle: 90° - Restricted projection length with 3,000 m mast height: elips4sun projection up to 5.1 m; square4sun projection up to 7.2 m	Height: - 3,000 mm - 3,500 mm	5,500 6,200

Rec. sales prices (net) in euros, exclusive of VAT | Pricing ex works | Prices exclusive of packaging, shipping, and installation costs.

This price list is subject to the latest version of our General Terms and Conditions (GTCs).

Additional equipment | Mast

No	Product	Description	Price in € per sail system
36	 Mast color	- Exclusively for ID 175, ID 110 - In desired RAL color, textured matte finish - Powder-coated	550
37	 V4A Maritime edition	- For ID 175, ID 110; interior stainless steel components in V4A - For IG 101, IG 211; mast and interior stainless steel components in V4A	2,100 1,100
38	 V4A Maritime edition	For free-standing roller tube bracket	550
39	Crank-operated internal height adjustment	Vertical adjustability of 2,000 mm starting at mast head. (Adjustability limited to 1,000 mm for sails starting at a length of 6,500 mm)	1,000 (per mast system)

Fastening | Installation elements

No.	Product	Description	Price in € per item
Roller tube			
40	Wall mount for roller tube installation	Standard, 2 pcs.	Inclusive
41	Wall mount for roller tube installation	Special design with different arm lengths	320
42	Free-standing roller tube bracket for single sail system	Design 01: rectangular	2,450
43	Free-standing roller tube bracket for single sail system	Design 02: cranked	4,050
44	Free-standing roller tube bracket for double-sail system	Design 03: with offset roller tube	3,700
45	Free-standing roller tube bracket for double-sail system	Design 04: without offset roller tube	3,700
46	Fastening set for installation on concrete base	For free-standing roller tube bracket	125
47	Fastening set for installation on Krinner	- For free-standing roller tube bracket - 2x Krinner KSF F 140 × 1600-M also required	1,100
ID 110 mast			
48	Wall bracket	2 pcs. required per mast	320
49	Anchoring set	- Components for anchoring the mast - For Krinner KSF G 66 × 650 or concrete base - For mast heights of 3,500 mm and up	200
50	Ground sleeve for installation in concrete base	- incl. assembly aid	200

Fastening | Installation elements

No.	Product	Description	Price in € per item
ID 175 mast			
51	Wall bracket front	Front fastening 2 pcs. required per mast	320
52	Wall bracket lateral	Lateral fastening 2 pcs. required per mast	320
53	Mast console – spacer	- e.g. for roof terraces - Individual height	650
54	Anchoring set	- Components for anchoring the mast - For Krinner KSF G 66 × 650 or concrete base - For mast heights of 4,000 mm and up	200
55	Fastening set for installation on concrete base		95
56	Fastening set for installation on Krinner		40
57	Krinner ground screw	- For mast fastening - KSF F 140 × 1600-M 1.6 m	410
IG 101 mast			
58	T-shape wall brackets	2 pcs. required per mast	320
59	Complete fastening set	comprising nos. 60 and 61	495
60	Krinner ground screw	- For mast fastening - KSF E 140 × 1600-E76-100 1.6 m	410
61	Krinner eccentric set E100		85
IG 211 mast			
62	C4sun Cube	- V2A stainless steel - With internal frame for mast fixing, but without filling - for mast heights of 3,000 mm	2,350
63	Mast console – spacer	- e.g. for roof terraces - Individual height	650
64	Fastening set for installation on concrete base	For 3,000 mm mast height	70
65	Fastening set for installation on concrete base	For 3,500 mm mast height	130
66	Fastening set for installation on Krinner	- Incl. flange plate and screw connection - Without Krinner ground screw	440
67	Krinner ground screw	- For mast fastening - KSF F 140 × 1600-M 1.6 m	410
68	Flange plate for installation on Krinner	Required	430
Fastening sets for installing wall mounts or 2 wall brackets			
69	Fischer installation set for concrete walls	- Incl. anchor rods M12 x 150 mm, injection mortar, perforated sleeves, screws, and accessories	90
70	Fischer installation set for thermal insulation system	- Incl. Thermax 12/110 M12, injection mortar, perforated sleeves, screws, and accessories	340
71	Fischer installation set for thermal insulation system	- Incl. Thermax 16/170 M12, injection mortar, perforated sleeves, screws, and accessories	370

Motor | Drive | Control and safety

No.	Product	Description	Price in € per item
Somfy io system Remote controlled			
72	Sunea 60 io 120/12 tube motor	STN cable – 1 m, black	Inclusive depending on version
73	Situo 1 io Pure remote control	1-channel handheld remote control	Inclusive depending on version
74	Situo 5 io Pure remote control	5-channel handheld remote control	110
75	Situo 5 Variation A/M io Pure remote control	Required for item no. 79 and 80	135
76	Smooove A/M IN io Pure shine wall-mounted transmitter	- With pushbuttons, incl. frame - Required for item no. 79 and 80	90
77	Eolis Wire Free io wind sensor	Battery-operated	150
78	Eolis io wind sensor	Wired, 230 V	210
79	Sunis Wire Free II io sun sensor	Situo 5 Variation remote control or Smooove A/M io Pure shine wall switch required	120
80	Rain sensor Ondeis 230 V	additionally required: nos. 78 and 75 or 76	245
81	Tahoma Switch	Somfy Smart Home Control Center	255
Somfy RTS System Remote controlled * **			
Applies for the international market only!	0.1 Tube Motor Altus 60 RTS 120/17	1m STN cable black	Inclusive depending on version
	0.2 Remote Control Telis 1 RTS Pure	1 channel handheld remote control	Inclusive depending on version
	0.3 Remote Control Telis 4 RTS Pure	5 channel handheld remote control	145
	0.4 Remote Control Telis 4 Soliris RTS	- 5 channel handheld remote control - required for RTS wind/sun sensor	165
	0.5 Soliris Sensor RTS LED	- Wind and sun sensor - wired, requires a wired 230 V connection	255
	0.6 Eolis Sensor RTS LED	- Wind sensor - wired, requires a wired 230 V connection	205
	0.7 Wall-Mounted Control Smooove 1 IN RTS	- 1 channel wireless control switch - Battery-operated - for Smooove covering frame (excluded)	90
Somfy LT system Wired On-site KNX (bus) control possible			
82	LT 60 Taurus 120/12 tube motor***	STN cable – 1 m, black	Inclusive depending on version
83	Wind and sun sensor “Soliris Uno complete kit”	- With switch, but without frame - Wired, no batteries required - Programming via switch	330
84	Soliris Smooove IB+ Pure	- Automatic time, wind, and sun function, incl. wind and sun sensor - Wired, no battery - 1x Smooove Uno IB+ required per drive - Incl. Smooove Pure frame	355
85	Individual motor controller “Smooove Uno IB+ Pure shine”	- Wall switch - Wired - “Pure shine” color	260
86	Smooove Pure cover frame		5

* Alternative radio-controlled option when Somfy io cannot be used. ** Differs from the German price list; special offer for international customers.

*** Integration into existing KNX (bus) systems possible; control via smart home solution.

Rec. sales prices (net) in euros, exclusive of VAT | Pricing ex works | Prices exclusive of packaging, shipping, and installation costs.

This price list is subject to the latest version of our General Terms and Conditions (GTCs).

No.	Product	Description	Price in € per item
Power package* **			
87	Junction box* WITHOUT Slim Receiver	Comprising: - 2x LT 60 Taurus 120/12 tube motor - Tandem control unit IP44, control of two motors - Drive cable 1 m and 10 m	775
88	Junction box WITH Slim Receiver io	As 84 plus: - Slim Receiver io plug - Situo 1 io Pure remote control, 1 channel	995
For int. market only	0.8 Exterior Junction Box WITH Slim Receiver RTS**	consisting of: - 2 tube motors LT 60 Taurus 120/12 - dual IP66 control unit, control of two motors - 1 m and 10 m drive cables - Slim Receiver RTS - remote control Telis 1 RTS Pure, 1 channel	1,040
	89 Housing for outdoor installation	- Aluminum housing in gray - Waterproof	90

Additional features

No.	Product	Description	Price in € per item
90	Radiator	- 1,500 watts, IP65 - With durable Ultra Glow heating tubes - Incl. wall mount	480
91	Clew shortening for elips4sun	Reduction of minimum mast distance	550
92	Rope deflection	- V2A castor with wall mount, but without fastening material - Can be used for rope deflection from sailcloth to mast	760

Service

No.	Product	Description	Price in €
Waterproofing & maintenance			
93	Sail cleaning, waterproofing & maintenance	- Not including disassembly/assembly - Customer required to ship sail (without profiles)	235 plus €23.00 per m²

* Power package recommended for larger sail surfaces or locations with high wind speeds; provided inclusive with sail dimensions marked red (see page 2).

** Differs from the German price list; special offer for international customers.

Rec. sales prices (net) in euros, exclusive of VAT | Pricing ex works | Prices exclusive of packaging, shipping, and installation costs.

This price list is subject to the latest version of our General Terms and Conditions (GTCs).



01/2023 Note: Subject to change without notice

BAHAMA®